

FLOW Wireless Video Transmission

3GSDI & HDMI | 5GHz DFS Comply | Strong wall-cross | Chip encryption



FLOW500

3GSDI&HDMI 500ft/150m



FLOW2000

3GSDI&HDMI 2000ft/600m





Both SDI&HDMI in Compact Size

The Same compact size for transmitter and receiver, with NP-F DV plates and new high gain antennas.



Transmitter

Receiver



Multicast and Double Encryption

Support 1 transmitter to 4 receivers reliable multicast mode. The transmitter and receivers are paired and double encrypted by private transmission protocol and by AES128, in order to protect the footages.





Anti-interference Transmission

With built-in wireless frequency scanner, the system will automatically jump to a best wireless channel

from 5.1 to 5.9GHz, based on current surroundings, to ensure a reliable and anti-interference transmission. You can also switch the wireless

channels manually. The OLED displays video format and

wireless signal strength. Support DFS (Dynamic Frequency Selection)





Strong Wall-Cross Performance

Featured stronger wall-cross performance that will keep video transmission without data lost or crash comparing to regular 5GHz wireless transmitters.



Reclock and Color Reproduction

To ensure the quality of black level, signal noise and color reproduction of the wireless received signal, the Flow series wireless receiving supports signal re-clock and accurate color reproduction.







http://www.swit.cc

Email: contact@swit.cc

Email: info@swit-europe.com