

SWIT

Rainproof Flexible LED Light

IP54 certificated Light Head, Controller and Battery



SL-100P 100W Flexible SMD-LED



SL-150P 150W Flexible SMD-LED



Flexible Textile SMD



The flexible LED lights SL-100P and SL-150P adopt foldable textile of SMD-LED light head, with high bright output and 2700-6500K continuous adjustment. The foldable design has reduced package size and enhanced the LED reliability.

Model	Power	Color Temp	Illuminance
SL-100P	100W	2700K-6500K	2800Lux @ 1 meter
SL-150P	150W	2700K-6500K	3700Lux @ 1 meter




Light Controller

The light controller can be connected to both SL-100P and SL-150P light head, provides LCD display, V-mount battery plate, DMX IN and OUT, and 5V USB power out for wireless DMX adaptor.



IP54 Rainproof

Both the flexible light head and the light controller are certificated IP54 rainproof, working together with SWIT IP54 rainproof V-mount batteries, you can put the light in rain at any angle without additional protections.



Light head **IP54 Rainproof**



Light controller **IP54 Rainproof**

Recommended V-mount Batteries



PB-R160S+ 160Wh battery

IP54 Rainproof




PB-R290S+ 290Wh battery


IP54 Rainproof

High CRI & TLCI

With high end SMD LEDs, the flexible lights have great performance on color rendition. The CRI Ra scores 98, and TLCI scores 99.




SL-100P SL-150P CCT=6500K_Dimmer=100%: CCT = D6218 (-0.1)
TLCI-2012 : 99 (D6218)



Television Lighting Consistency Index-2012

Sector	Lightness	Chroma	Hue
R	0	0	0
Ry	0	0	0
Y	0	0	0
YG	0	0	0
G	0	0	0
Gc	0	0	0
C	0	0	0
Cb	0	0	0
B	0	0	0
Bm	0	0	0
M	0	0	0
MR	0	0	0



Accessories



X-bracket and rotatable light stand connector



Light stand clamp



Optional Purchase

Ball diffuser
Model # LA-DS100 for SL-100P
Model # LA-DS150 for SL-150P



Optional Purchase

Eggcrate diffuser box
Model # LA-BS100 for SL-100P
Model # LA-BS150 for SL-150P

Specifications

Model	SL-100P	SL-150P
LED	560pcs SMD LEDs	840pcs SMD LEDs
Power	100W	150W
Illuminance	2800Lux @ 1m	3700Lux @ 1m
Color temp	2700 - 6500K	2700 - 6500K
Color render	CRI 98; TLCI 99	CRI 98; TLCI 99
Input voltage	DC 11 - 36V	DC 11 - 36V
Dimension	Light: 600×470mm; Controller: 239×112×72mm	Light: 600×690mm; Controller: 239×112×72mm
Weight	Light: 0.4kg; Controller: 1.06kg	Light: 0.7kg; Controller: 1.06kg

